



FLAT INSTALLATION CABLES

VF 2224 TWIN FLAT

✓ MOBILE ✓ STUDIO ✓ INSTALLATION ✓ STAGE



APPLICATION

VF 2224 cable is designed to be used in Broadcast system and mobile installations where flat cables are required. This cable is specially suitable for connecting two channel XLR connection professional stage and studio operation

CONSTRUCTION DATA

Core Numbers x Section	2 x 2 x 0,22 mm ² (AWG 24)
Stranded Copper Conductor	28 x 0,10 mm ø Stranded Bare Copper
Conductor Insulation	1,50 ± 0,05 mm ø XLPE
Conductor Color Code	Blue / Red
Shielding 1 st	Copper spiral shielding
Shielding 2 nd	Copper spiral shielding
Shielding Factor	100%
Outer Sheath	sPVC
Outer Diameter	3,5 x 7,4 mm ø
Weight	4.1 kg/100 m

ELECTRICAL DATA

Conductor Resistance	< 86 Ω / km
Shield Resistance	< 22 Ω / km
Insulation Resistance	> 2000 MΩ x km
Capacitance	core/core
	core/screen
	80 pF / m
	135 pF / m

MECHANICAL DATA

Minimum bending radius	10x D (D= outer diameter)
Temperature range	
Mobile installation	- 5° C to + 70° C
Fixed installation	-30° C to + 70° C

■ BLACK

